

### PVR20



#### SPECIFICATION

12 volt 14 amp/hour at C20 rate  
1200 peak amps  
545 amps cranking current for 5 seconds  
185 amps CCA 30 seconds to 7.2v @ -18C  
Reserve capacity 18 minutes @ 25 amps to 10.5v  
Terminals M6 female  
Operating temp range -40°C to +45°C

Amp	14Ah
Dimensions (hxwxd)	176mm x 84mm x 130mm
CCA	545A
Peak	1200A
Weight	4.9kg

**Pure lead maintenance free drycell battery featuring TPT (thin plate technology). The construction concept was originally developed for military aircraft requiring very high power delivery for short durations achieved through the use of extremely thin plates.**

Exceptionally good anti-vibration properties with fast recharge capability and recovery from heavy discharge. Can be mounted upright or flat. Design life of 8–10 years.

This battery is a standard fit on many jet skis and quad bikes where vibration resistance is appreciated. Sealed construction and small size enable mounting in many locations including footwells. This battery is ideal for track cars with engine sizes up to 2.0 litre.

- Maintenance-free, sealed
- Voltage 12 volts
- 1200 peak amps
- 545 amps cranking current
- 14 amp/hour capacity
- Lightweight 4.9Kg
- Motorcycle, motorsport, kit car